01234 215407 • SALES@BANNER-UK.COM
WWW.SWAGINGMACHINES.COM

BS16C PORTABLE



- Assembles up to -16 (DN25) 2SN.
- A lightweight portable machine for workshop and maintenance use.
- Easy to set and use.
- For use on a wide range of hose and fittings.

The annular BS16C offers a compact, high performance hose assembly press that is suitable for maintenance, workshop, agricultural, mobile or breakdown standby use – built to the usual high standards that you have come to expect from Banner.

The BS16C is supplied as standard with a range of 5 quick to fit die sets - 16, 20, 23, 29 and 35mm - covering spiral hose assembly from -04 (DN6) to -16 (DN25). All dies come in a purpose built plastic toolbox with the machine. Extra Dies available - 6, 8, 10, 12, 14, 18, 26 and 39mm. Cluster quick change dies are also available with this machine.

Machine setting and adjustment is simple. The swage size setting is achieved by adjusting the direct reading micrometer type gauge. Select and fit the appropriate dies, set the machine to the required finished diameter and then operate the cam pump with rechargeable drill or mains drill if required until the gauge setting is reached.

STANDARD/CLUSTER DIE SETS

Code	Swage Range	L(mm)
16	16-20	62
20	20-23	62
23	23-26	62
29	29-35	62
35	35-39	62

EXTRA DIE SETS

6	6-8	62
8	8-10	62
10	10-12	62
12	12-14	62
14	14-16	62
18	18-20	62
26	26-29	62
39	39-46	62

SPECIFICATIONS

Capacity	-16 (DN25) 2SN
Actuator	Single acting spring return 70 tonne ram
Pump	Integral 1 speed cam pump with rechargeable drill 2500 rpm (not included)
Standard dies	16, 20, 23, 29 and 35mm
Extra dies	6, 8, 10, 12, 14, 18, 26 and 39mm Flared one piece dies and special form are available.
General	Maximum die length = 62mm Maximum swage diameter = 55mm Max opening over die = die + 24mm Die holder throat (open) = 70mm
Crated details	45 × 46 × 36cm(h) Gross weight 45kg